

## Spring pullers load capacity 0.0–2.5 kg

Type 7200, cable extension 1600 mm, rustproof

# AUTOSTAT

### Application

For the ergonomic support of assembly operations. Spring pullers keep tools close at hand at all times during assembly and at the same time ensure that the workplace is tidy. The spring balances are designed in such a way that each work tool is automatically pulled back to the original position after use. Suitable for lightweight tools.

### Version

- housing made of extremely impact-resistant special plastic
- Cable drum is made of non-abrasive plastic
- High-strength special motive spring
- Simple load setting secured against incorrect operation
- cable feed limitation is impact absorbing and adjustable
- the load is attached via a safe snap hook
- Suspension with screw snap hook
- Safety device: Fall arrester in line with DIN 15112 included in scope of delivery, insulated suspension, shape-stabilised structure
- Working area: Cable extraction: 1600 mm, ropes in special lengths available on request

### Advantage

- Effortless work



<b>Art. No.</b>	<b>77001 595</b>
<b>Min./max. load-carrying capacity</b>	1.2-2.5 kg
<b>Model</b>	7200/2
<b>With overrotation protection</b>	No
<b>Number of springs</b>	1 PCS
<b>Spring design</b>	Special mainspring
<b>Spring breakage protection</b>	No
<b>Max. cable pull-out length</b>	1600 mm
<b>Adjustable cord length</b>	No
<b>Wire cable diameter</b>	2 mm
<b>Replaceable cord</b>	No
<b>Cord in-feed restriction</b>	Absorbs impacts, adjustable
<b>Cable drum material</b>	Abrasion-proof plastic
<b>Cord material</b>	Stainless Steel
<b>With automatic locking</b>	No
<b>Suspension type</b>	Freely rotating and pivot screw karabiner hook
<b>Load attachment</b>	Karabiner hook
<b>Material of the housing</b>	Plastic
<b>Housing height</b>	134.3 mm
<b>Housing width</b>	108 mm
<b>Housing thickness</b>	36.7 mm
<b>Version</b>	All external components made of non-rusting material
<b>Height</b>	420 mm
<b>DIN</b>	15112

### EAN-Code

4053625360338